



**NEW KSYRIUM PRO DISC**

The legendary Ksyrium Pro, smartly adapted to Road Disc, for the most epic rides

**Road disc optimized**

- Disc specific rim shape
- Disc friendly spoke geometry and lacing
- Brake torque resistant hubs, including 15 mm front compatibility

**Light where it matters**

- New extra light ISM 4D rims
- Light and strong Zicral spokes

**Efficient, comfortable and durable**

- Isopulse lacing for superior stiffness under high lateral loads
- New 25 mm Yksion Pro tyres, featuring GripLink / PowerLink concept
- Proven Ksyrium reliability

PAIR	<b>1535 g</b>
FRONT	<b>680 g</b>
REAR	<b>855 g</b>
TYRE 700x25	<b>210 g</b>

**FEATURES**

**VERSIONS**

- Clincher 6 bolts M11
- Clincher 6 bolts ED11
- Clincher Center Lock M11

**RIMS**

- Material: Maxtal
- Height: 26mm, asymmetrical
- Joint: SUP
- Drilling: Fore
- Disc brake specific profile
- Weight reduction: ISM 4D
- Valve hole diameter: 6.5 mm
- Tyre: clincher
- ETRTO size: 622x15C
- Recommended tyre sizes: 21 to 30 mm

**SPOKES**

- Material: Zicral
- Shape: straight pull, bladed
- Nipples: Fore integrated aluminum
- Count: 20 front and rear
- Lacing: front crossed 2, rear Isopulse

**DELIVERED WITH**

- BX601 quick releases (V24 503 01 frt, V24 504 01 rear)
- Front QR adapters (129 827 01, B41 043 01 for road wheel since MY16)
- Rear QR adapters (308 731 01 for ITS4 and TS2, B49 894 01 for ID360)
- Specific disc bolts (308 719 01)
- Multifonction adjustment wrench (325 423 01)
- User guide

**HUBS**

- Front body: carbon with aluminum flanges
- Rear body: aluminum
- Axle material: aluminum
- Adjustable sealed cartridge bearings
- Freewheel: FTS-L steel
- Front: Quick release, 12 thru and 15 thru compatible

**TYRE**

- Yksion Pro GripLink (front) & PowerLink (rear)
- Front and Rear Tread: Single Compound
- Casing: 127 TPI
- Breaker: Front Kevlar, Rear nylon
- Dimension: 25-622 (700x25c)
- Max. Pressure: 25mm 7.7 bars - 110 PSI

